



ADW MACHINERY



www.adwmachinery.com

Meet The **Movexx** Family



RR1000-S



TT1000-T-CP



TT1000-L



TT2500-L



TT1000-M-Inox-EB



TT1000-M



TT1500-T



TT1500-S



TT1000-F



TT2500-S-Push



TT2500-S



TT2500-S-AT



TT3500-S



TT3500-S-AT



TT1000-T



TT0450-M



CC2500-S



TT3500-S-Push



TT1000-T-Basic



RR3500-S



TT6000-S



AA1000-S-Guided



AA1000-S-Flexible



AA1000-UR-Guided



AA2500-S-Guided



AA2500-S-Flexible



TT1000-T-Inox



TT1500-M-SR



RR1000-S-Inox



TT1500-T-Inox



TT1000-T-Cleanroom



TT1500-T-Cleanroom



TT2500-S-Cleanroom



TT6000-S-Cleanroom



TT500-S-HH

TT1500-T

The TT1500-T can easily move trolleys, carts, and server racks with a total weight of 1.500 kg.

Specifications

Power
DC motor 24V, 600W

Maximum pulling power and speed
Up to 1.500 KG 4 km/h

Battery
Exchangeable Lithium LiFePo4 battery 24V

Tires
Full rubber 250 x 85 mm

Weight and length
130 kg 1274 mm 487 mm

Work height
1006, 1137, 1231 mm



The TT1500-T is an electric tug that can easily move trolleys, carts and server racks with a total weight of 1.500 kg. Because of the exchangeable hook system, the TT1500-T can move a wide range of carts and trolleys, such as server racks, roll containers, industrial carts, and waste containers.



As long as the wheel configuration of the trolley consists of 2 fixed wheels and 2 steering wheels, or 2 fixed wheels and 4 steering wheels, the TT1500-T is capable to move these. The TT1500-T is standard supplied with Lithium technology. This machine also makes use of our unique exchangeable battery system, which enables you to quickly and simply change the empty battery for a full one.

RR1000-S

The RR1000-S is mostly used in the logistical distribution in combination with Milk run systems.

Specifications

Power

DC motor 24V, 420W

Maximum pulling power and speed

Up to 1.000 kg 6,5 km/h

Battery

Exchangeable Lithium LiFePo4 battery 24V

Tires

Full rubber 250 x 85 mm

Weight and length

130 kg 1230 mm 454 mm

Work height

1082, 1174, 1223 mm



A Movexx RR1000-S is a standing variant of the TT1000-T, and ideal to use for longer distances. This electric tug can easily move trolleys, industrial carts, or roll containers on wheels, without you having to perform any physical exercise. The RR1000-S has an exchangeable battery system. An empty battery can be easily changed by moving the battery from the holder and inserting a charged battery.

The electric tug has two adjustable speeds (fast and slow), an adjustable pole, an adjustable back support, a claxon, and anti-tip wheels. Furthermore, you are standing on a checker plate for maximum grip. Because of the useful coupling mechanism, almost every load on wheels can be pulled.

TT2500-S-AT

This Movexx smart electric tug is an all-round powerhouse.

This Movexx smart electric tug is an all-round powerhouse.

Specifications

Power
DC motor 24V, 800W

Maximum pulling power and speed
Up to 2.500kg 4,5 km/h

Battery
Built-in Lead acid battery 24V

Tires
Pneumatic 406 x 165 mm

Weight and length
300 kg 1160 mm 845 mm

Work height
820 - 1210 mm (variable)



There was a growing demand from the market whether Movexx could offer a solution for moving waste containers from underground storage areas of apartment complexes. The TT2500-S-AT was initially developed for this application but in practice is suitable for many other purposes. For example, this machine is also ideal for moving trailers and caravans in outdoor areas.

With its large ground clearance and massively implemented pneumatic tyres, this machine is ideally suited for the transition area from an indoor to outdoor area. With its 2.500 kg capacity, it can be used on many sites.

Challenge us to show what the TT2500-S-AT can do for your organisation and request a no-obligation on-site demo.

MOVEXX APPLICATIONS



Airport



Datacenters



Food & Pharma



Healthcare & Laundry



Hospitality & Events



Industry



Retail & Distributions



Retail & Distributions

Meet The Ksf Family



Scissor Lifter **PLX 400**



Person lifter **PL500 / PL650 / PL800 / PL950**



Super lifter **CA 400**



Material lifter **BD1 / BD2**



Material lifter **BD400**



Cargo Lifter **ES550 / ES700 / ES850**



Portable lifter **CM340 / CM520 / CM270 / CM439 / CM369**



Glass Lifter **GL550 / GL700 / GL850**



Glass Robot **GRM250**



Material lifter **AL330**



Gas Bottle Lifter



Glass Trolley **SGT2**



Glass Trolley **GT1 / GT2**



Material lifter **ML1 / ML2**



CF Wall Cutter

SCISSOR LIFTER

KSF Scissor Lifter is perfect for installation / repair of

- 1. Power by hydraulic system, compact and reliable.
- 2. Compact design, width only 55 cm easy to roll through a standard doorway.
- 3. Easy transport and move to next job site.
- 4. Safety Emergency Stop Button.
- 5. Manually lowering the platform in case of power failure is equipped.

Hospital / Warehouse | Hotel | Shopping mall | Construction | School
Temple | Airport | Factory | Auditorium



Specifications

Model	PLX-300S	PLX-400S
Voltage	220V / 110V / DC12V	220V / 110V / DC12V
Platform Height	298 cm (9,78 ft)	380 cm (12,47 ft)
Working Height	500 cm (16,4 ft)	600 cm (19,69 ft)
Machine Height	175 cm (69 in)	185 cm (73 in)
Load Capacity	200 kg(441 lbs)	180 kg (397lbs)
Basic Size	125 x 60 cm (50 x 24 in)	125 x 60 cm (50 x 24 in)
Platform Size	123 x 55 cm (48 x 22 in)	123 x 55 cm (48 x 22 in)

PERSON LIFTER

Your Solution for Overhead Installations and Repairs!

- 1. Patent – retractable holder.
- 2. High-speed motor with double insulation design.
- 3. Slip-Clutch system: adjustable slip-clutch system to protect the mechanism while core bit get stuck.
- 4. Variable speed power switch, can operate with soft start.
- 5. Motor overload circuit protector.
- 6. Optional accessories : Tool box , Water collector



Specifications

Spec/Model	PL-500	PL-650	PL-800	PL-950
Voltage	220V	220V	220V	220V
Lifting height 500 cm (16 ft)	500 cm (16 ft)	650 cm (21 ft)	800 cm (26 ft)	950 cm (31 ft)
Working height	700 cm (23 ft)	850 cm (28 ft)	1000 cm (33 ft)	1150 cm (38 ft)
Load capacity	130 kg (287 lbs)	130 kg (287 lbs)	130 kg (287 lbs)	110 kg (243 lbs)
Operating size	198*170 cm (78*67 in)	198*170 cm (78*67 in)	198*170 cm (78*67 in)	233*198 cm (92*78 in)
Stowed height	198 cm (78 in)	198 cm (78 in)	198 cm (78 in)	198 cm (78 in)
Stowed size	118*77 cm (46*30 in)	118*77 cm (46*30 in)	118*77 cm (46*30 in)	125*77 cm (49*30 in)
Platform height	120 cm (47 in)	120 cm (47 in)	120 cm (47 in)	120 cm (47 in)
Platform size	60*66 cm (24*26 in)	60*66 cm (24*26 in)	60*66 cm (24*26 in)	60*66 cm (24*26 in)
Machine weight	297 kg (655 lbs)	320 kg (705 lbs)	344 kg (758 lbs)	385 kg (849 lbs)

KSF APPLICATIONS



- Hospitals • Warehouses • Hotels • Shopping malls • Construction
- Schools • Temples/Churches • Airports • Factorys • Auditoriums • HVAC Contractors
- Electrical Contractors • Industrial Maintenance • Steel Frame Erection • Facilities Maintenance



ADW MACHINERY

MACHINERY Retail & Servicing Division
of ADMIRAL WORLD GENERAL TRADING LLC

OUR BRANDS

movexx
smart electric tugs



CTE
WORK BECOMES EASY

HG

OUR ADDRESS:

ADMIRAL WORLD GENERAL TRADING LLC P.O BOX 112661 STR.8
SHOWROOM 24, AL QUOZ 1, DUBAI, UNITED ARAB EMIRATES

M +971 56 408 2339

machinery@admiralworld.com

